AT 625 - Technische Daten

Description

Der Reifen AT 625 ist für Baggerlader und Kompaktlader konzipiert und eignet sich hervorragend für alle Einsatzarten in der Landwirtschaft, Grabe- und Ladevorgänge. Er ist auch die ideale Wahl für die Zuckerrohrernte und bietet die Zuverlässigkeit, die Sie benötigen, um die ganze Saison über produktiv zu bleiben. Dank seines extra tiefen Laufflächendesigns sind mit dem AT 625 eine erhöhte Widerstandsfähigkeit gegen Durchschläge und Haltbarkeit gewährleistet, sodass Sie schwierige Bedingungen mit Zuversicht bewältigen können. Dieser Reifen bietet hervorragende Traktion und Stabilität, kombiniert mit verbesserter Schnitt- und Abriebfestigkeit, was ihn zu einem langlebigen und zuverlässigen Partner für Ihre landwirtschaftlichen Aufgaben macht.

UM

International Standard

Construction

BIAS

Machinery

Landwirtschaft: Erntemaschine
Industrie: Baggerlader • Kompaktlader

Version	STANDARD
Type	TL
Tyre Size	14.9 - 24
LI/SS	145 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	400
Overall Diameter (mm)	1265
Static Loaded Radius (mm)	575
Rolling Circumference (mm)	3800
Rim Rec	DW 13
Rim Alt	DW 11 ; DW 12 ; DW 13 L
TRA Code	R4

Load capacity (Kg)

km/h / bar	2.90
40	2900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12.10.2024 09:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..