

AW 09 - Technische Daten



Description

AW 09 wurde für die Bodenbearbeitung, die Heuernte und Transportanwendungen mit landwirtschaftlichen Geräten, Heupressen und Anhängern entwickelt. Er ist ideal für die moderne Landwirtschaft auf und abseits der Straße. Seine verstärkte Karkasse gewährleistet hohe Tragfähigkeit und ein längeres Reifenleben. AW 09 wurde mit einer speziellen, durchstichfesten Gummimischung entwickelt, die hervorragenden Widerstand gegen Stoppeln bietet.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Heupresse • Mähdrescher •
Landwirtschaftliche Geräte • Anhänger

Version	STANDARD
Type	TL
Tyre Size	260/70 - 15.3
LI/SS DRIVE WHEEL	114 A8
LI/SS FREE ROLLING	126 A8

Dimensions US Standard

Usa code	94037841
Section Width (inch)	10.6
Overall Diameter (inch)	29.6
Static Loaded Radius (inch)	13.2
Rolling Circumference (inch)	86.9
Rim Rec	9.00
ECE	E4-106R-000373

Load capacity (lbs)

mph / psi	52
5 FR	5250
15 FR	4460
20 FR	4200
25 FR	3750
5 DW	3640
15 DW	3100
20 DW	2910
25 DW	2600

Printed on 26.04.2024 10:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..