

AW-18 - Technische Daten



Description

AW-18 wurde für Anhänger und Anbaugeräte zur Bodenbearbeitung entwickelt. Sein spezielles Design mit richtungsunabhängigen Laschen und einem abgerundeten Schulterbereich vermeidet Ernteschäden beim Manövrieren. Das Laufflächenprofil wurde speziell entwickelt, um beste Selbstreinigungseigenschaften zu gewährleisten. AW-18 steht auch für besten Fahrkomfort und reduzierten Kraftstoffverbrauch.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Landwirtschaftliche Geräte

Version	STANDARD
Type	TL
Tyre Size	11.5/80 - 15.3 (300/80 - 15.3)
LI/SS FREE ROLLING	139 A8

Dimensions US Standard

Usa code	94064045
Section Width (inch)	11.7
Overall Diameter (inch)	33.3
Rim Rec	9.00
ECE	E11-106R-006020

Load capacity (lbs)

mph / psi	69
5 FR	7500
15 FR	6380
20 FR	6000
25 FR	5360

Printed on 24.04.2024 07:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..