

AW 702 IND - Datenblatt



Description

AW 702 IND wurde für Anwendungen mit industriellen entwickelt. Dieser Reifen für schwere Betriebsbedingungen wurde von BKT für eine neue Dimension der Beständigkeit entworfen.

UM

US Standard

Construction

❖ BIAS

Machinery

Industrie: Anhänger

SIZE	Version	USACode	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
6.00 - 16	INDUSTRIAL	94054206	103 A8	8	4.00 E	4.50 E ; 4½ K	6.7	28.4	13.3	84.6	TT	E11-106R-004358

Printed on 29.04.2024 11:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..