

## AW 705 - Technische Daten



### Description

AW 705 wurde zum Einsatz mit landwirtschaftlichen Geräten, Anhängern und Heupressen für die Bodenbearbeitung und Transportanwendungen entwickelt. Er ist ideal für die moderne Landwirtschaft dank verbesserter Beständigkeit und hoher Tragfähigkeit.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Heupresse • Landwirtschaftliche Geräte • Anhänger

Version	SPECIAL
Type	TL
Tyre Size	15.0/55 - 17
LI/SS FREE ROLLING	134 A8

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	381
Overall Diameter (mm)	850
Static Loaded Radius (mm)	391
Rolling Circumference (mm)	2575
Rim Rec	13.00
Rim Alt	13 ; W 13
ECE	E11-106R-004250

## Load capacity (Kg)

km/h / bar	2.60
10 FR	2970
25 FR	2525
30 FR	2375
40 FR	2120

Printed on 26.04.2024 20:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..