

AW 705 - Technische Daten



Description

AW 705 wurde zum Einsatz mit landwirtschaftlichen Geräten, Anhängern und Heupressen für die Bodenbearbeitung und Transportanwendungen entwickelt. Er ist ideal für die moderne Landwirtschaft dank verbesserter Beständigkeit und hoher Tragfähigkeit.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Heupresse • Landwirtschaftliche Geräte • Anhänger

Version	STANDARD
Type	TL
Tyre Size	15.0/70 - 18
LI/SS FREE ROLLING	148 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	405
Overall Diameter (mm)	1010
Static Loaded Radius (mm)	447
Rolling Circumference (mm)	3092
Rim Rec	13.00
Rim Alt	13 ; W 13
ECE	E4-106R-001903

Load capacity (Kg)

	km/h / bar	3.60
	10 FR	4410
	25 FR	3750
	30 FR	3530
	40 FR	3150

Printed on 26.04.2024 18:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..