

AW 705 - Technische Daten



Description

AW 705 wurde zum Einsatz mit landwirtschaftlichen Geräten, Anhängern und Heupressen für die Bodenbearbeitung und Transportanwendungen entwickelt. Er ist ideal für die moderne Landwirtschaft dank verbesserter Beständigkeit und hoher Tragfähigkeit.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Heupresse • Landwirtschaftliche Geräte • Anhänger

| | |
|--------------------|--------------|
| Version | SPECIAL |
| Type | TL |
| Tyre Size | 16.0/70 - 20 |
| LI/SS FREE ROLLING | 154 A8 |

Dimensions International Standard

| | |
|----------------------------|----------------------|
| Ply Rating | 14 |
| Section Width (mm) | 408 |
| Overall Diameter (mm) | 1075 |
| Static Loaded Radius (mm) | 480 |
| Rolling Circumference (mm) | 3155 |
| Rim Rec | 13.0 |
| Rim Alt | 12 SDC ; 13 SDC ; 14 |
| ECE | E11-106R-004252 |

Load capacity (Kg)

| | km/h / bar | 3.50 |
|--|------------|------|
| | 10 FR | 5250 |
| | 25 FR | 4465 |
| | 30 FR | 4200 |
| | 40 FR | 3750 |

Printed on 26.04.2024 23:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..