

## AW 708 - Technische Daten

### Description

AW 708 wurde für Bodenbearbeitung, Transport und Heuernte-Anwendungen mit landwirtschaftlichen Geräten, Anhängern und Heupressen entwickelt. Es ist auch eine „HD“ Version mit besonders schnitt- und reißfester Gummimischung erhältlich.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Heupresse • Landwirtschaftliche Geräte • Anhängen  
Industrie: Anhänger



|                    |              |
|--------------------|--------------|
| Version            | STANDARD     |
| Type               | TL           |
| Tyre Size          | 19.0/45 - 17 |
| LI/SS FREE ROLLING | 148 A8       |

## Dimensions US Standard

|                              |                |
|------------------------------|----------------|
| Usa code                     | 94010257       |
| Ply Rating                   | 18             |
| Section Width (inch)         | 18.5           |
| Overall Diameter (inch)      | 34.1           |
| Static Loaded Radius (inch)  | 15             |
| Rolling Circumference (inch) | 99.8           |
| Rim Rec                      | 16.00          |
| ECE                          | E4-106R-002268 |

## Load capacity (lbs)

| mph / psi | 48   |
|-----------|------|
| 5 FR      | 9720 |
| 15 FR     | 8270 |
| 20 FR     | 7780 |
| 25 FR     | 6940 |

Printed on 23.04.2024 13:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..