

AW 708 - Technische Daten



Description

AW 708 wurde für Bodenbearbeitung, Transport und Heuernte-Anwendungen mit landwirtschaftlichen Geräten, Anhängern und Heupressen entwickelt. Es ist auch eine „HD“ Version mit besonders schnitt- und reißfester Gummimischung erhältlich.

UM

International Standard

Construction

✚ BIAS

Machinery

Landwirtschaft: Heupresse • Landwirtschaftliche Geräte • Anhängern
Industrie: Anhänger

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	149 A8

Dimensions International Standard

Ply Rating	18
Section Width (mm)	405
Overall Diameter (mm)	875
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2564
Rim Rec	AG 13.00

Load capacity (Kg)

km/h / bar	4.50
10 FR	4550
25 FR	3870
30 FR	3640
40 FR	3250

Printed on 22.04.2024 05:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..