

AW 708 - Technische Daten



Description

AW 708 wurde für Bodenbearbeitung, Transport und Heuernte-Anwendungen mit landwirtschaftlichen Geräten, Anhängern und Heupressen entwickelt. Es ist auch eine „HD“ Version mit besonders schnitt- und reißfester Gummimischung erhältlich.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Heupresse • Landwirtschaftliche Geräte •
Anhänger
Industrie: Anhänger

Version	STANDARD
Type	TL
Tyre Size	500/50 - 17
LI/SS FREE ROLLING	149 A8

Dimensions US Standard

Usa code	94010370
Ply Rating	14
Section Width (inch)	19.7
Overall Diameter (inch)	37.2
Static Loaded Radius (inch)	16.4
Rolling Circumference (inch)	108.3
Rim Rec	16.00
ECE	E4-106R-001813

Load capacity (lbs)

mph / psi	41
5 FR	10030
15 FR	8530
20 FR	8020
25 FR	7160

Printed on 22.04.2024 05:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..