

## AW 726 - Technische Daten



### Description

AW 726 wurde speziell für Anhänger bei Anwendungen zum Transport entwickelt. Er eignet sich sowohl zum Straßeneinsatz als auch abseits der Straße. AW 726 zeichnet sich durch hervorragende Performance auf der Straße und beste Selbstreinigungseigenschaften aus. Das Blockmuster gewährleistet ein langes Reifenleben.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Anhänger

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS DRIVE WHEEL	137 A8
LI/SS FREE ROLLING	149 A8

## Dimensions International Standard

Ply Rating	18
Section Width (mm)	400
Overall Diameter (mm)	875
Rim Rec	AG 13.00
ECE	E11-106R-005341

## Load capacity (Kg)

km/h / bar	4.50
10 FR	4550
25 FR	3870
30 FR	3640
40 FR	3250
10 DW	3220
25 DW	2735
30 DW	2575
40 DW	2300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09.12.2024 10:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..