

AW 726 - Technische Daten



Description

AW 726 wurde speziell für Anhänger bei Anwendungen zum Transport entwickelt. Er eignet sich sowohl zum Straßeneinsatz als auch abseits der Straße. AW 726 zeichnet sich durch hervorragende Performance auf der Straße und beste Selbstreinigungseigenschaften aus. Das Blockmuster gewährleistet ein langes Reifenleben.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Anhänger

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS DRIVE WHEEL	137 A8
LI/SS FREE ROLLING	149 A8

Dimensions US Standard

Usa code	94054008
Ply Rating	18
Section Width (inch)	15.7
Overall Diameter (inch)	34.4
Rim Rec	AG 13.00
ECE	E11-106R-005341

Load capacity (lbs)

mph / psi	65
5 FR	10030
15 FR	8530
20 FR	8020
25 FR	7160
5 DW	7100
15 DW	6030
20 DW	5680
25 DW	5070

Printed on 27.04.2024 10:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..