

AW 726 - Technische Daten



Description

AW 726 wurde speziell für Anhänger bei Anwendungen zum Transport entwickelt. Er eignet sich sowohl zum Straßeneinsatz als auch abseits der Straße. AW 726 zeichnet sich durch hervorragende Performance auf der Straße und beste Selbstreinigungseigenschaften aus. Das Blockmuster gewährleistet ein langes Reifenleben.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Anhänger

Version	STANDARD
Type	TL
Tyre Size	420/55 - 17
LI/SS DRIVE WHEEL	121 A8
LI/SS FREE ROLLING	133 A8

Dimensions International Standard

Section Width (mm)	415
Overall Diameter (mm)	890
Static Loaded Radius (mm)	392
Rolling Circumference (mm)	2584
Rim Rec	13.00
ECE	E11-106R-005265

Load capacity (Kg)

	km/h / bar	2.00
	10 FR	2885
	25 FR	2450
	30 FR	2305
	40 FR	2060
	10 DW	2030
	25 DW	1725
	30 DW	1625
	40 DW	1450

Printed on 27.04.2024 07:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..