# AW 909 - Technische Daten

## Description

AW 909 wurde für die Bodenbearbeitung, Heuernte und Transportanwendungen mit landwirtschaftlichen Geräten, Anhängern und Heupressen entwickelt. Er ist ideal für die moderne Landwirtschaft auf und abseits der Straße.

## UM

International Standard

## Construction

BIAS

## Machinery

Landwirtschaft: Heupresse • Landwirtschaftliche Geräte • Anhänger

| | |
|---|---|
| **Version** | STANDARD |
| **Type** | TL |
| **Tyre Size** | 10.0/75 - 15.3 |
| **LI/SS FREE ROLLING** | 135 A8 |

## Dimensions International Standard

| | |
|---|---|
| **Ply Rating** | 18 |
| **Section Width (mm)** | 274 |
| **Overall Diameter (mm)** | 760 |
| **Static Loaded Radius (mm)** | 343 |
| **Rolling Circumference (mm)** | 2227 |
| **Rim Rec** | 9.00 |
| **ECE** | E4-106R-001880 |

## Load capacity (Kg)

| km/h / bar | 7.10 |
|---|---|
| **10 FR** | 3050 |
| **25 FR** | 2595 |
| **30 FR** | 2440 |
| **40 FR** | 2180 |

Printed on 26.04.2024 14:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..