

BK 208 - Technische Daten



Description

BK 208 eignet sich für Transportanwendungen mit Anhängern und Leicht-LKWs. Er ist ein äußerst beständiger und zuverlässiger Reifen zum Einsatz auf dem Feld und auf der Straße.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Kompaktraktor • Leicht-Lkw • Anhänger

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

Dimensions International Standard

Ply Rating	16
Section Width (mm)	212
Overall Diameter (mm)	810
Rim Rec	6.00 G

Load capacity (Kg)

	km/h / bar	7.60
	100 LS	1600
	100 LD	1400

Printed on 25.04.2024 17:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..