

## BK 208 - Datenblatt



### Description

BK 208 eignet sich für Transportanwendungen mit Anhängern und Leicht-LKWs. Er ist ein äußerst beständiger und zuverlässiger Reifen zum Einsatz auf dem Feld und auf der Straße.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Kompakttraktor • Leicht-Lkw • Anhänger

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type
7.50 - 16	STANDARD	94013234	12	6.00 G		8.3	31.9	TT
7.50 - 16	STANDARD	94013241	14	6.00 G		8.3	31.9	TT
7.50 - 16	STANDARD	94013258	16	6.00 G		8.3	31.9	TT

Printed on 25.04.2024 20:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..