

## BK 6060 - Technische Daten



### Description

BK 6060 ist ein Reifen, der sich sowohl zum Einsatz auf dem Feld als auch auf der Straße mit Anhängern und Baggerladern für den Transport sowie für Bagger- und Ladeanwendungen eignet. Dieser Reifen mit Blockprofil sichert ein langes Reifenleben.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrie: Baggerlader • Anhänger

Version	INDUSTRIAL
Type	TT
Tyre Size	9.00 - 16

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	255
Overall Diameter (mm)	925
Static Loaded Radius (mm)	427
Rolling Circumference (mm)	2740
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E11-106R-004362

## Load capacity (Kg)

km/h / bar	7.25
30	2300

Printed on 08.06.2023 14:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..