

BK 826 - Technische Daten



Description

BK 826 wurde speziell für Anhänger in Transportanwendungen entworfen. Er ist ein Diagonalreifen, der dank seiner verstärkten Karkasse mit hoher Tragfähigkeit aufwartet. BK 826 ist auch in Ausführung „industrial“ mit besonderer Durchstichfestigkeit erhältlich und eignet sich so für Baggerlader.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Anhänger

Industrie: Baggerlader • Anhänger

Version	STANDARD
Type	TT
Tyre Size	8.25 - 16

Dimensions International Standard

Ply Rating	14
Section Width (mm)	238
Overall Diameter (mm)	863
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E4-54R-0024095

Load capacity (Kg)

km/h / bar	6.90
100 LS	1745
100 LD	1650

Printed on 20.04.2024 10:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..