

BK RUF N TUF - Technische Daten



Description

BK RUF N TUF ist ein Reifen mit Blockprofil, der sich besonders für Transportarbeiten mit Anhängern und Leicht-LKWs eignet. Er ist ideal zum Straßeneinsatz und bietet ausgezeichnete Beständigkeit.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Leicht-Lkw • Anhänger

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

Dimensions International Standard

Ply Rating	8
Section Width (mm)	216
Overall Diameter (mm)	830
Rim Rec	6.00 G
Rim Alt	5.50 F

Load capacity (Kg)

	km/h / bar	4.15
	100 LS	1120
	100 LD	975

Printed on 19.04.2024 20:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..