

BK RUF N TUF - Technische Daten



Description

BK RUF N TUF ist ein Reifen mit Blockprofil, der sich besonders für Transportarbeiten mit Anhängern und Leicht-LKWs eignet. Er ist ideal zum Straßeneinsatz und bietet ausgezeichnete Beständigkeit.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Leicht-Lkw • Anhänger

Version	STANDARD
Type	TL
Tyre Size	7.50 - 16

Dimensions US Standard

Usa code	94059133
Ply Rating	14
Section Width (inch)	8.5
Overall Diameter (inch)	32.7
Rim Rec	6.00 G
Rim Alt	5.50 F

Load capacity (lbs)

	mph / psi	--
	--	--
	--	--

Printed on 19.04.2024 18:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..