

## BOGMAX - Technische Daten



### Description

BOGMAX wurde speziell für Geländeanwendungen entwickelt. Das besonders tiefe Laufflächenprofil bietet hervorragende Traktion, während der Flankenschutz äußere Einwirkungen und das Risiko möglicher Schäden reduziert. BOGMAX ist ein 6-lagiger Reifen mit M+S-Technologie – perfekt für sportliche Leistungen unter jeglichen Bedingungen.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Geländefahrzeug

Version	STANDARD
Type	TL
Tyre Size	AT 30 X 10 - 14
LI/SS	58 F

## Dimensions US Standard

Usa code	94052851
Ply Rating	6
Section Width (inch)	10.2
Overall Diameter (inch)	29.9
Rim Rec	7.0 AT
Rim Alt	7.5 AT ; 8.0 AT

## Load capacity (lbs)

mph / psi	7
50	520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07.12.2024 15:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..