

COMMANDER 3 RIB - Technische Daten



Description

COMMANDER 3 RIB ist ein Vorderreifen mit 3-fachem Rippenprofil, der zur Bodenbearbeitung und zum Transport entwickelt wurde. Er bietet erstklassige Beständigkeit und Tragfähigkeit dank der optimierten Lastenverteilung auf Mittel- und Schulterrippen. Die robuste Karkasse sowie die gegen Stoppeln resistente Gummimischung bieten hervorragende Durchstoßfestigkeit.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: 2WD-Traktor

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 7.50 - 16 |
| LI/SS | 99 A8 |

Dimensions US Standard

| | |
|-------------------------|-----------------------|
| Usa code | 4304380454 |
| Ply Rating | 8 |
| Section Width (inch) | 8.3 |
| Overall Diameter (inch) | 31.9 |
| Rim Rec | 5.50 F |
| Rim Alt | 5.00 F ; 5 K ; 6.00 F |
| TRA Code | F2 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 56 |
| 25 | 1710 |

Printed on 12.08.2024 14:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..