

COMMANDER (F) - Technische Daten



Description

COMMANDER (F) ist ein Reifen mit 3-fachem Rippenprofil – perfekt zur Bodenbearbeitung und für Transportanwendungen. Die tiefe Lauffläche aus einer schnitt- und reißfesten Gummimischung sichert ein längeres Reifenleben, sowie hohe Tragfähigkeit.

UM

International Standard

Construction

✚ BIAS

Machinery

Landwirtschaft: 2WD-Traktor

Version	STANDARD
Type	TT
Tyre Size	6.00 - 16
LI/SS	94 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	175
Overall Diameter (mm)	750
Static Loaded Radius (mm)	357
Rolling Circumference (mm)	2308
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5.00 F
ECE	E11-106R-003001
TRA Code	F2

Load capacity (Kg)

km/h / bar	4.50
30	670

Printed on 24.04.2024 17:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..