

COMMANDER (F) - Datenblatt



Description

COMMANDER (F) ist ein Reifen mit 3-fachem Rippenprofil – perfekt zur Bodenbearbeitung und für Transportanwendungen. Die tiefe Lauffläche aus einer schnitt- und reißfesten Gummimischung sichert ein längeres Reifenleben, sowie hohe Tragfähigkeit.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: 2WD-Traktor

| SIZE | Version | TRA Code | LI/SS | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | TKPH | ECE |
|-----------|----------|----------|--------|----|---------|--------------------------|-----|-----|-----|------|------|------|-----------------|
| 5.50 - 16 | STANDARD | F2 | 86 A6 | 6 | 4.00 E | 3.50D ; 4.50E | 155 | 720 | 340 | 2145 | TT | 1 | E11-106R-003308 |
| 6.00 - 16 | STANDARD | F2 | 94 A6 | 8 | 4.50 E | 4.00 E ; 5.00 F | 175 | 750 | 357 | 2308 | TT | 0 | E11-106R-003001 |
| 6.50 - 16 | STANDARD | F2 | 98 A6 | 8 | 4.50 E | 4.00 E ; 5.00 F ; 5.50 F | 183 | 770 | 362 | 2332 | TT | 1 | E11-106R-004107 |
| 6.50 - 16 | STANDARD | F2 | 102 A6 | 10 | 4.50 E | 4.00 E ; 5.00 F ; 5.50 F | 183 | 770 | 362 | 2332 | TT | 1 | E11-106R-004109 |
| 7.50 - 16 | STANDARD | F2 | 103 A6 | 8 | 5.50 F | 5.00 F ; 5 K ; 6.00 F | 210 | 810 | 376 | 2433 | TT | 1 | E11-106R-004116 |

Printed on 25.04.2024 00:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..