

COMMANDER (R) - Technische Daten



Description

COMMANDER (R) ist ein Landwirtschaftsreifen, der sich durch ein tiefe Lauffläche mit kraftvollen Hochstollen für ein längeres Reifenleben auszeichnet. Das spezielle Stollenmuster mit zweifachem Winkel verleiht sowohl ausgezeichnete Traktion auf dem Feld als auch beste Selbstreinigungseigenschaften. Die robuste Karkasse ist aus einer schnitt- und reißfesten Gummimischung hergestellt, die mit besserer Durchstichfestigkeit neben erstklassiger Tragfähigkeit aufwartet. COMMANDER (R) ist der perfekte Reifen zur Bodenbearbeitung sowie für Transport- und Erntearbeiten.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Erntemaschine • Traktor

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 12.4 - 24 |
| LI/SS | 128 A6 |

Dimensions International Standard

| | |
|-----------------------------------|-----------------|
| Ply Rating | 12 |
| TKPH | 1 |
| Section Width (mm) | 328 |
| Overall Diameter (mm) | 1180 |
| Static Loaded Radius (mm) | 569 |
| Rolling Circumference (mm) | 3669 |
| Rim Rec | W 11 |
| Rim Alt | W 10 |
| ECE | E11-106R-004365 |
| TRA Code | R1 |

Load capacity (Kg)

| | |
|-------------------|-------------|
| km/h / bar | 3.5 |
| 30 | 1800 |

Printed on 25.04.2024 23:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..