

COMMANDER TWIN RIB - Technische Daten



Description

COMMANDER TWIN RIB ist ein Reifen mit 4-fachem Rippenprofil, dessen Schulterkerben ausgezeichnete Haftung bieten. Das breitere Reifenprofil gewährleistet eine gute Gewichtverteilung. Die robuste Karkasse sowie die erstklassige Gummimischung stehen für ein längeres Reifenleben. COMMANDER TWIN RIB ist perfekt zur Bodenbearbeitung und für Transportanwendungen.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: 2WD-Traktor

Version	STANDARD
Type	TT
Tyre Size	5.00 - 15
LI/SS	82 A6

Dimensions International Standard

Ply Rating	6
TKPH	1
Section Width (mm)	145
Overall Diameter (mm)	665
Rim Rec	4.00 E
TRA Code	F2

Load capacity (Kg)

km/h / bar	3.70
30	475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 15.10.2024 02:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..