

COMMANDER TWIN RIB - Technische Daten



Description

COMMANDER TWIN RIB ist ein Reifen mit 4-fachem Rippenprofil, dessen Schulterkerben ausgezeichnete Haftung bieten. Das breitere Reifenprofil gewährleistet eine gute Gewichtsverteilung. Die robuste Karkasse sowie die erstklassige Gummimischung stehen für ein längeres Reifenleben. COMMANDER TWIN RIB ist perfekt zur Bodenbearbeitung und für Transportanwendungen.

UM

US Standard

Construction

❖ BIAS

Machinery

Landwirtschaft: 2WD-Traktor

Version	STANDARD
Type	TT
Tyre Size	6.50 - 16
LI/SS	90 A8

Dimensions US Standard

Usa code	94064618
Ply Rating	8
Section Width (inch)	7.1
Overall Diameter (inch)	30
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5.00 F ; 5.50 F
ECE	E11-106R-004107
TRA Code	F2

Load capacity (lbs)

mph / psi	62
25	1320

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 15.10.2024 01:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..