

## CON STAR - Technische Daten



### Description

CON STAR ist besonders zum Einsatz mit Kompaktladern und Teleskopladern für agro-industriellen Hebe- und Ladearbeiten geeignet. Er zeichnet sich durch hohe Tragfähigkeit kombiniert mit ausgezeichneter senkrechter und horizontaler Stabilität aus. CON STAR wurde aus einer schnitt- und reißfesten Gummimischung hergestellt, die zu einem verlängerten Reifenlebenszyklus beiträgt.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Kompaktlader • Teleskoplader

Industrie: Kompaktlader • Teleskoplader

Version	INDUSTRIAL
Type	TL
Tyre Size	340/80 - 20 (12.5/80 - 20)
LI/SS	144 A8

## Dimensions International Standard

Section Width (mm)	350
Overall Diameter (mm)	1065
Static Loaded Radius (mm)	491
Rolling Circumference (mm)	3272
SRI (mm)	500
Rim Rec	11
Rim Alt	12 ; 11 SDC ; 12 SDC ; W 10 ; W 11
ECE	E11-106R-003021

## Load capacity (Kg)

km/h / bar	4.00
40	2800

Printed on 08.12.2023 17:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..