

CON STAR - Technische Daten



Description

CON STAR ist besonders zum Einsatz mit Kompaktladern und Teleskopladern für agro-industriellen Hebe- und Ladearbeiten geeignet. Er zeichnet sich durch hohe Tragfähigkeit kombiniert mit ausgezeichneter senkrechter und horizontaler Stabilität aus. CON STAR wurde aus einer schnitt- und reißfesten Gummimischung hergestellt, die zu einem verlängerten Reifenlebenszyklus beiträgt.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Kompaktlader • Teleskoplader

Industrie: Kompaktlader • Teleskoplader

| | |
|-----------|-------------------------------|
| Version | INDUSTRIAL |
| Type | TL |
| Tyre Size | 400/70 - 20 (16.0/70 - 20) |
| LI/SS | 149 A8 |

Dimensions International Standard

| | |
|----------------------------|----------------------|
| Ply Rating | 16 |
| Section Width (mm) | 405 |
| Overall Diameter (mm) | 1080 |
| Static Loaded Radius (mm) | 501 |
| Rolling Circumference (mm) | 3303 |
| SRI (mm) | 525 |
| Rim Rec | 13 |
| Rim Alt | 12 SDC ; 13 SDC ; 14 |
| ECE | E11-106R-003024 |

Load capacity (Kg)

| km/h / bar | 4.00 |
|------------|------|
| 40 | 3250 |

Printed on 26.04.2024 05:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..