

CON STAR - Technische Daten



Description

CON STAR ist besonders zum Einsatz mit Kompaktladern und Teleskopladern für agro-industriellen Hebe- und Ladearbeiten geeignet. Er zeichnet sich durch hohe Tragfähigkeit kombiniert mit ausgezeichneter senkrechter und horizontaler Stabilität aus. CON STAR wurde aus einer schnitt- und reißfesten Gummimischung hergestellt, die zu einem verlängerten Reifenlebenszyklus beiträgt.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Kompaktlader • Teleskoplader

Industrie: Kompaktlader • Teleskoplader

Version	INDUSTRIAL
Type	TL
Tyre Size	440/80 - 24 (17.0/80 - 24)
LI/SS	168 A8

Dimensions International Standard

Ply Rating	22
Section Width (mm)	455
Overall Diameter (mm)	1315
Static Loaded Radius (mm)	610
Rolling Circumference (mm)	3986
SRI (mm)	625
Rim Rec	DW 14 L
Rim Alt	DW 13 ; DW 13 L ; DW 15 L
ECE	E11-106R-003027

Load capacity (Kg)

km/h / bar	5.00
40	5600

Printed on 26.04.2024 05:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..