

CONTAINER KING - Technische Daten



Description

CONTAINER KING wurde speziell für Reach-Stacker bei intermodalen Transportanwendungen und in der Logistik entwickelt. Dieser außergewöhnliche Reifen ist aus einer extrem verschleißfesten Gummimischung hergestellt, die Rissbildungen reduziert. CONTAINER KING gewährleistet ein verlängertes Reifenleben neben hervorragender Stabilität im Hebemodus.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Reach-Stacker

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 - 33

Dimensions US Standard

Usa code	94064526
Ply Rating	40
Overall Width (inch)	20.1
Overall Diameter (inch)	74.6
Static Loaded Radius (inch)	33.5
Rolling Circumference (inch)	229.1
Rim Rec	13.00/2.5
TRA Code	IND4

Load capacity (lbs)

mph / psi	145
5	59520

Printed on 24.04.2024 04:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..