

CRANE SPECIAL - Technische Daten



Description

CRANE SPECIAL eignet sich vortrefflich für Pick & Carry Kräne auf unebenen Böden. Der Reifen ist aus einer speziellen Gummimischung hergestellt, die hohe Stabilität und Beständigkeit verleiht.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Mobilkran

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 16.00 - 25 |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94040582 |
| Ply Rating | 28 |
| Overall Width (inch) | 18.2 |
| Overall Diameter (inch) | 58.5 |
| Static Loaded Radius (inch) | 26.9 |
| Rolling Circumference (inch) | 173 |
| Rim Rec | 11.25/2.0 |
| TRA Code | E3 |

Load capacity (lbs)

| | |
|-----------|-------|
| mph / psi | 83 |
| 30 | 14800 |

Printed on 02.12.2023 11:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..