

CRANE SPECIAL - Datenblatt



Description

CRANE SPECIAL eignet sich vortrefflich für Pick & Carry Kräne auf unebenen Böden. Der Reifen ist aus einer speziellen Gummimischung hergestellt, die hohe Stabilität und Beständigkeit verleiht.

UM

International Standard

Construction

 BIAS

Machinery

Industrie: Mobilkran

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 - 24	STANDARD	E3	24	10.00 W		375	1368	628	4050	TT
14.00 - 24	STANDARD	E3	24	10.00 W		375	1368	628	4050	TL
16.00 - 25	STANDARD	E3	28	11.25/2.0		463	1485	682	4395	TL
16.00 - 25	STANDARD	E3	28	11.25/2.0		463	1485	682	4395	TT
18.00 - 25	STANDARD	E3	32	13.00/2.5	15.00/2.5	510	1615	739	4780	TL

Printed on 23.04.2024 18:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..