

CRANE SPECIAL - Datenblatt



Description

CRANE SPECIAL eignet sich vortrefflich für Pick & Carry Kräne auf unebenen Böden. Der Reifen ist aus einer speziellen Gummimischung hergestellt, die hohe Stabilität und Beständigkeit verleiht.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Mobilkran

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 - 24	STANDARD	94043934	E3	24	10.00 W		14.8	53.9	24.7	159.4	TT
14.00 - 24	STANDARD	94041282	E3	24	10.00 W		14.8	53.9	24.7	159.4	TL
16.00 - 25	STANDARD	94040582	E3	28	11.25/2.0		18.2	58.5	26.9	173	TL
16.00 - 25	STANDARD	94041541	E3	28	11.25/2.0		18.2	58.5	26.9	173	TT
18.00 - 25	STANDARD	94041213	E3	32	13.00/2.5	15.00/2.5	20.1	63.6	29.1	188.2	TL

Printed on 23.04.2024 17:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..