

D 405 - Technische Daten



Description

D 405 ist ein Reifen zum vorwiegenden Einsatz auf der Straße und ideal für Transportanwendungen mit Anhängern und Leicht-LKWs. Eine ausgezeichnete Haftung auf der Straße sowie regelmäßiger Verschleiß resultieren in extra Beständigkeit.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Leicht-Lkw • Anhänger

Version	STANDARD
Type	TT
Tyre Size	10.50 - 16

Dimensions International Standard

Ply Rating	14
Section Width (mm)	290
Overall Diameter (mm)	980
Rim Rec	6.00 T

Load capacity (Kg)

	km/h / bar	6.90
	100 LS	2575
	100 LD	2300

Printed on 26.02.2024 03:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..