

D 405 - Technische Daten



Description

D 405 ist ein Reifen zum vorwiegenden Einsatz auf der Straße und ideal für Transportanwendungen mit Anhängern und Leicht-LKWs. Eine ausgezeichnete Haftung auf der Straße sowie regelmäßiger Verschleiß resultieren in extra Beständigkeit.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Leicht-Lkw • Anhänger

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

Dimensions International Standard

Ply Rating	16
Section Width (mm)	212
Overall Diameter (mm)	810
Rim Rec	6.00 G
Rim Alt	5.50 F
ECE	E4-54R-0022812

Load capacity (Kg)

	km/h / bar	7.60
	100 LS	1600
	100 LD	1400

Printed on 23.04.2024 15:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..