

DESERT KING - Technische Daten



Description

DESERT KING eignet sich am besten für lockere Böden, sandiges Gelände und Fertigeresätze mit Wüstenfahrzeugen. Das optimierte Laufflächendesign bietet hervorragenden Auftrieb und Richtungsstabilität. Sein starkes Nylongehäuse und die Hochleistungssicke wurden speziell für den Niederdruckbetrieb entwickelt. DESERT KING bietet auch eine hohe Widerstandsfähigkeit gegen Durchschläge und eine längere Lebensdauer der Reifen.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Wüsten-Truck

Version	STANDARD
Type	TL
Tyre Size	18.00 - 25 DT

Dimensions International Standard

Ply Rating	16
Section Width (mm)	470
Overall Diameter (mm)	1535
Static Loaded Radius (mm)	635
Rolling Circumference (mm)	4405
Rim Rec	10.00/1.5
TRA Code	E7

Load capacity (Kg)

	km/h / bar	2.50
	10	7500
	50	5150
	65	4375

Printed on 23.04.2024 14:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..