

DESERT KING - Technische Daten



Description

DESERT KING eignet sich am besten für lockere Böden, sandiges Gelände und Fertigeresätze mit Wüstenfahrzeugen. Das optimierte Laufflächendesign bietet hervorragenden Auftrieb und Richtungsstabilität. Sein starkes Nylongehäuse und die Hochleistungssicke wurden speziell für den Niederdruckbetrieb entwickelt. DESERT KING bietet auch eine hohe Widerstandsfähigkeit gegen Durchschläge und eine längere Lebensdauer der Reifen.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Wüsten-Truck

Version	STANDARD
Type	TL
Tyre Size	29.5 - 25 DT

Dimensions International Standard

Ply Rating	28
Section Width (mm)	770
Overall Diameter (mm)	1822
Static Loaded Radius (mm)	786
Rolling Circumference (mm)	5392
Rim Rec	25.00/3.5
TRA Code	E7

Load capacity (Kg)

	km/h / bar	2.50
	10	13200
	50	10000
	65	8250

Printed on 23.04.2024 15:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..