

DON 2000 - Technische Daten



Description

DON 2000 eignet sich besonders für Transportarbeiten mit Anhängern und Leicht-LKWs auf und abseits der Straße. Er bietet extra Beständigkeit in Kombination mit starker Leistung während des gesamten Produktlebenszyklus.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Leicht-Lkw • Anhänger

Version	STANDARD
Type	TT
Tyre Size	11.00 - 20

Dimensions US Standard

Usa code	94067725
Ply Rating	18
Section Width (inch)	11.5
Overall Diameter (inch)	43.7
Static Loaded Radius (inch)	20.5
Rolling Circumference (inch)	134.4
Rim Rec	8.0
Rim Alt	7.5 ; 8.5

Load capacity (lbs)

mph / psi	120	110
62 LS	7390	-
62 LD	-	6610

Printed on 28.04.2024 22:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..