

EARTHMAX SR 22 - Technische Daten



Description

EARTHMAX SR 22 (G-2/L-2) ist ein **All Steel** Radialreifen, der speziell für Planierer und Lader entworfen wurde, die bei extremen Winterverhältnissen auf Schnee und Eis im Einsatz sind. Bediener werden die ausgezeichnete Traktion und Stabilität durch das nicht richtungsgebundene Profil der Lauffläche zu schätzen wissen.

UM

US Standard

Construction

 RADIAL

Machinery

Industrie: Planierer • Planierer • Radlader
OTR: Planierer • Planierer • Radlader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	14.00 R 24
LI/SS	153 A8/175 A2

Dimensions US Standard

Usa code	94048816
Overall Width (inch)	14.4
Overall Diameter (inch)	53.9
Static Loaded Radius (inch)	24.6
Rolling Circumference (inch)	163
Rim Rec	8.00 TG
Rim Alt	9.00 GR , 10.00 VA
Star Rating	*
TRA Code	G2/L2

Load capacity (lbs)

mph / psi	29	33	36	40	44	47	51	54	76	80
25	4940	5360	5840	6150	6600	7150	7400	8050	-	-
5	-	-	-	-	-	-	-	-	14800	15200

Printed on 11.12.2023 19:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..