

EARTHMAX SR 22 - Technische Daten



Description

EARTHMAX SR 22 (G-2/L-2) ist ein **All Steel** Radialreifen, der speziell für Planierer und Lader entworfen wurde, die bei extremen Winterverhältnissen auf Schnee und Eis im Einsatz sind. Bediener werden die ausgezeichnete Traktion und Stabilität durch das nicht richtungsgebundene Profil der Lauffläche zu schätzen wissen.

UM

International Standard

Construction

 RADIAL

Machinery

Industrie: Planierer • Planierer • Radlader

OTR: Planierer • Planierer • Radlader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	167 B/182 A2

Dimensions International Standard

Overall Width (mm)	452
Overall Diameter (mm)	1350
Static Loaded Radius (mm)	590
Rolling Circumference (mm)	3950
Rim Rec	14.00/1.5
Star Rating	**
TRA Code	E2/L2

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50
50	4375	4625	4750	5000	5150	5450	--	--	--	--	--
10	--	--	--	--	--	7300	7500	7750	8000	8250	8500

Printed on 26.04.2024 12:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..