

## EARTHMAX SR 22 - Technische Daten



### Description

EARTHMAX SR 22 (G-2/L-2) ist ein **All Steel** Radialreifen, der speziell für Planierer und Lader entworfen wurde, die bei extremen Winterverhältnissen auf Schnee und Eis im Einsatz sind. Bediener werden die ausgezeichnete Traktion und Stabilität durch das nicht richtungsgebundene Profil der Lauffläche zu schätzen wissen.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industrie: Planierer • Planierer • Radlader  
OTR: Planierer • Planierer • Radlader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	167 B/182 A2

## Dimensions US Standard

Usa code	94052387
Overall Width (inch)	17.8
Overall Diameter (inch)	53.1
Static Loaded Radius (inch)	23.2
Rolling Circumference (inch)	155.5
Rim Rec	14.00/1.5
Star Rating	**
TRA Code	E2/L2

## Load capacity (lbs)

mph / psi	58	62	65	69	73	76	80	83	87	91	94
30	9650	10200	10500	11000	11400	12000	--	--	--	--	--
5	--	--	--	--	--	16100	16500	17100	17600	18200	18700

Printed on 26.04.2024 04:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..