

EARTHMAX SR 22 - Technische Daten



Description

EARTHMAX SR 22 (G-2/L-2) ist ein **All Steel** Radialreifen, der speziell für Planierer und Lader entworfen wurde, die bei extremen Winterverhältnissen auf Schnee und Eis im Einsatz sind. Bediener werden die ausgezeichnete Traktion und Stabilität durch das nicht richtungsgebundene Profil der Lauffläche zu schätzen wissen.

UM

International Standard

Construction

 RADIAL

Machinery

Industrie: Planierer • Planierer • Radlader
OTR: Planierer • Planierer • Radlader

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 20.5 R 25 |
| LI/SS | 177 B/193 A2 |

Dimensions International Standard

| | |
|----------------------------|-----------|
| Overall Width (mm) | 525 |
| Overall Diameter (mm) | 1490 |
| Static Loaded Radius (mm) | 640 |
| Rolling Circumference (mm) | 4315 |
| Rim Rec | 17.00/2.0 |
| Rim Alt | 17.00/1.7 |
| Star Rating | ** |
| TRA Code | E2/L2 |

Load capacity (Kg)

| km/h / bar | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 | 6.50 |
|------------|------|------|------|------|------|------|-------|-------|-------|-------|-------|
| 50 | 5800 | 6150 | 6500 | 6700 | 6900 | 7300 | - | - | - | - | - |
| 10 | - | - | - | - | - | 9750 | 10000 | 10300 | 10900 | 11200 | 11500 |

Printed on 08.12.2023 20:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..