

EARTHMAX SR 22 - Technische Daten



Description

EARTHMAX SR 22 (G-2/L-2) ist ein **All Steel** Radialreifen, der speziell für Planierer und Lader entworfen wurde, die bei extremen Winterverhältnissen auf Schnee und Eis im Einsatz sind. Bediener werden die ausgezeichnete Traktion und Stabilität durch das nicht richtungsgebundene Profil der Lauffläche zu schätzen wissen.

UM

US Standard

Construction

 RADIAL

Machinery

Industrie: Planierer • Planierer • Radlader
OTR: Planierer • Planierer • Radlader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	177 B/193 A2

Dimensions US Standard

Usa code	94052431
Overall Width (inch)	20.7
Overall Diameter (inch)	58.7
Static Loaded Radius (inch)	25.2
Rolling Circumference (inch)	169.9
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7
Star Rating	**
TRA Code	E2/L2

Load capacity (lbs)

mph / psi	58	62	65	69	73	76	80	83	87	91	94
30	12800	13600	14300	14800	15200	16100	-	-	-	-	-
5	-	-	-	-	-	21500	22000	22700	24000	24700	25400

Printed on 08.12.2023 20:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..