

EARTHMAX SR 22 - Technische Daten



Description

EARTHMAX SR 22 (G-2/L-2) ist ein **All Steel** Radialreifen, der speziell für Planierer und Lader entworfen wurde, die bei extremen Winterverhältnissen auf Schnee und Eis im Einsatz sind. Bediener werden die ausgezeichnete Traktion und Stabilität durch das nicht richtungsgebundene Profil der Lauffläche zu schätzen wissen.

UM

International Standard

Construction

 RADIAL

Machinery

Industrie: Planierer • Planierer • Radlader
OTR: Planierer • Planierer • Radlader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	185 B/201 A2

Dimensions International Standard

Overall Width (mm)	610
Overall Diameter (mm)	1614
Static Loaded Radius (mm)	709
Rolling Circumference (mm)	4863
Rim Rec	19.50/2.5
Star Rating	**
TRA Code	E2/L2

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50
50	7500	7750	8250	8500	9000	9250	-	-	-	-	-
10	-	-	-	-	-	12500	12850	13200	13600	14000	14500

Printed on 11.12.2023 20:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..