

EARTHMAX SR 23 - Technische Daten



Description

EARTHMAX SR 23 (G-2/L-2) ist ein All Steel Radialreifen, der speziell für Planierer und Lader entworfen wurde. Der Reifen zeichnet sich durch hervorragende Traktionseigenschaften vorne und seitlich sowie ausgezeichnete Selbstreinigung aus. Die robuste Karkasse und die besonders schnittfeste Lauffläche gewährleisten eine lange Lebensdauer.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Planierer • Radlader

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 20.5 R 25 |
| LI/SS | 161 A8/186 A2 |

Dimensions International Standard

| | |
|----------------------------|-----------|
| Overall Width (mm) | 535 |
| Overall Diameter (mm) | 1490 |
| Static Loaded Radius (mm) | 668 |
| Rolling Circumference (mm) | 4489 |
| Rim Rec | 17.00/2.0 |
| Star Rating | * |
| TRA Code | G2/L2 |

Load capacity (Kg)

| km/h / bar | 1.25 | 1.50 | 1.75 | 2.00 | 2.25 | 2.50 | 2.75 | 3.00 | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 |
|------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 40 | 2430 | 2800 | 3150 | 3450 | 3875 | 4125 | 4375 | 4625 | -- | -- | -- | -- | -- |
| 10 | -- | -- | -- | -- | -- | -- | -- | -- | 8000 | 8250 | 8750 | 9000 | 9500 |

Printed on 17.04.2024 22:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..