

EARTHMAX SR 33 PLUS - Datenblatt



Description

EARTHMAX SR 33 PLUS ist ein Radialreifen mit einem mehrfachen Blockmuster der Lauffläche, das speziell entwickelt wurde, um ausgezeichnete Traktion auf weichem, sandigem oder schlammigem Boden zu bieten. Die robuste Karkasse mit Stahlbändern zeichnet sich durch exzellente Beständigkeit sowie Schnitt- und Durchstoßfestigkeit aus. Neben optimalen Selbstreinigungseigenschaften verleiht EARTHMAX SR 33 PLUS hervorragende Stabilität.

UM

International Standard

Construction

 RADIAL

Machinery

Industrie: Universelles Fahrzeug

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
16.00 R 20	STANDARD	173/170 G	11.25	10.00W, 10.0	448	1310	582	3974	TL	E11-54R-0017916

Printed on 09.05.2024 11:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..