

EARTHMAX SR 33 - Technische Daten



Description

Earthmax SR 33 ist ein Radialreifen für Mehrzweckfahrzeuge. Das besondere Blockmuster der Lauffläche wurde speziell entwickelt, um ausgezeichnete Traktion auf weichem, sandigem oder schlammigem Boden zu bieten. Neben optimalen Selbstreinigungseigenschaften verleiht Earthmax SR 33 hervorragende Stabilität. Die robuste All-Steel Karkasse zeichnet sich durch exzellente Dauerhaftigkeit sowie Schnitt- und Durchstoßfestigkeit aus.

UM

US Standard

Construction

 RADIAL

Machinery

Industrie: Universelles Fahrzeug

Version	STANDARD
Type	TL
Tyre Size	365/80 R 20 (14.5 R 20)
LI/SS	152 K

Dimensions US Standard

Usa code	94061907
Overall Width (inch)	14.2
Overall Diameter (inch)	43.1
Static Loaded Radius (inch)	19.5
Rolling Circumference (inch)	130.6
Rim Rec	11
ECE	E11-54R-0017314

Load capacity (lbs)

mph / psi	90
68	7850

Printed on 23.04.2024 10:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..