

EARTHMAX SR 35 - Technische Daten



Description

Earthmax SR 35 ist ein radialer All Steel Niederquerschnittsreifen, der speziell für knickgelenkte Muldenkipper und Radlader entworfen wurde. Er eignet sich vortrefflich für Arbeiten, die hervorragende Traktion und Flotation erfordern. Dank der robusten Karkasse mit Stahlbändern verleiht der Reifen außergewöhnliche Dauerhaftigkeit sowie Widerstandsfähigkeit gegenüber Rissen und Stichen.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Knickgelenkter Muldenkipper • Planierer • Radlader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	875/65 R 29 (35/65 R 29)
LI/SS	214 A2

Dimensions International Standard

Overall Width (mm)	890
Overall Diameter (mm)	1860
Static Loaded Radius (mm)	816
Rolling Circumference (mm)	5559
Rim Rec	27.00/3.50
Rim Alt	27.00/3.0, 28.00/3.5
Star Rating	*
TRA Code	L3

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75
10	18500	19500	20600	21200

Printed on 02.05.2024 01:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..