

EARTHMAX SR 43 - Technische Daten



Description

Earthmax SR 43 (L-4) ist ein radialer All-Steel-Reifen, der speziell für Radlader entwickelt wurde, die in extrem felsiger Umgebung vor allem in Untertagebau zum Einsatz kommen. Der Reifen zeichnet sich durch hervorragende Leistungen bei Lade- und Transportarbeiten im Tagebau, in Steinbrüchen sowie auf Schrottplätzen aus. Das einzigartige Laufflächenmuster verleiht optimale Traktion und Stabilität. Dank seiner All-Steel-Struktur gewährleistet der robuste Earthmax SR 43 (L-4) erstklassige Stich- und Schnittfestigkeit sowie ein verlängertes Reifenleben.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Radlader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	216 A2

Dimensions US Standard

Usa code	94063291
Overall Width (inch)	30.9
Overall Diameter (inch)	73.8
Static Loaded Radius (inch)	33.3
Rolling Circumference (inch)	222.2
Rim Rec	25.00/3.5
Star Rating	**
TRA Code	L4

Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	41900	43000	44100	45400	46700	49400

Printed on 15.05.2024 06:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..